

#### DESCRIPTION:

A unique final decorative water-based paint that is manufactured based on acrylic emulsion and special-effect dyes to give undulating metallic colors and different effects depending on the viewing angle, giving the walls aesthetics and luxurious elegance.

#### CHARACTERISTICS:

- Unique appearance resembling flower petals.
- Excellent adhesion and high durability.
- Good washability and excellent color fastness.
- Superior resistance to water and household chemicals.
- Formula free of formaldehyde, ammonia and APEO.
- Wide range of colors.

#### RECOMMENDED USE:

It is used for interior applications on concrete, cement and gypsum surfaces of palaces, offices, galleries, hotels, restaurants...etc.

#### PHYSICAL CONSTANTS:

- Metallic appearance
- Color according to the colors of the "Time Amouage" catalogue.
- Specific gravity 1.12, ASTM D1475
- Viscosity: High viscosity, ASTM D562
- Theoretical diffusion rate\* (5-7) m<sup>2</sup>/liter
- the exams:
- Stability to freezing passing, ASTM D2243
- Stability to heat passing, ASTM D2243
- Chemical resistance (household detergents), ASTM D1306
- Water resistance passes ASTM D870
- VOC value: 14.78 g/L, ASTM D2369, UAE METS
- VOC Emission Test after Application: Pass, LEED Requirements-Ver.4, UAE/METS

#### APPLICATION INSTRUCTIONS:

- The temperature during application must not be less than 5°C, the surface humidity must not exceed 8%, and the ambient relative humidity must not exceed 70%.
- The surface alkalinity must not exceed (Ph=9).
- The paint must be stirred well before use.
- Do not paint over wet surfaces until they are completely dry
- Do not paint the next layer unless the previous layer dries completely, taking into account the minimum time interval between painting the two layers.
- Adequate ventilation should be provided during application

APPLICATION TOOLS:

- Spray gun: Suggested nozzle size: (1.5 – 1.8) mm
- Roller: Suggested type: Soft wool roller
- Brush: the good and appropriate type

THINNER:

- Do not dilute
- Ready to use

THINNING RATIO:

- Do not dilute
- Ready to use

CLEANING TOOLS:

Tap Water.

APPLICATION GUIDE:

- Apply one layer of "Time Sealerin".
- Apply two coats of "Time Putty".
- Apply one or two layers of "Time D Silk Primer" in the same color as "Time Amouage".
- Apply two layers of "Time Amwaj" (at an angle), then apply one layer using the recommended special trowel in the same direction to give the desired shape.

PACKING:

US Gallon 3 ltr

SHELF LIFE:

In sealed container: 12 months in dry, cool and well ventilated place

SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
  - Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
  - It is recommended to use the product in well-ventilated places or use artificial ventilation
  - The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.