

#### DESCRIPTION:

A high-quality, semi-gloss decorative paint with a distinctive appearance, slow-drying, based on modified resin preparations.

#### CHARACTERISTICS:

- Gives distinctive decorative designs on the walls.
- Sufficient drying time to implement the required design.
- Excellent adhesion strength and high durability.
- Wide range of colors

#### RECOMMENDED USE:

It is used for interior applications on concrete, cement and gypsum surfaces in homes, hotels and wedding halls.

#### PHYSICAL CONSTANTS:

- The appearance is semi-glossy.
- Color according to Time Paints color catalogue.
- Specific gravity 0.9 ASTM D1475
- Viscosity is 84 Krebs units ASTM D562
- Solid size 30% ASTM D2697
- Dry layer thickness: The layer thickness varies depending on the application method.
- Theoretical spread rate\* depends on the form of the required decorative application, the thickness of the layer, and the nature of the surface.
- Flash point 39°C
- \*The practical spread rate of the applied product depends on the nature of the surface, ambient conditions, method of application, thickness of the actual dry layer of the product, and rate of wastage.
- (To avoid waste, you must make sure - upon purchase - of the appropriate amount of paint for the surfaces to be painted).

#### DRYING TIME:

- Surface drying for 3 hours.
- Complete dryness for 12 hours.
- Previous results under ASTM 5895D at 25°C.

#### APPLICATION TOOLS:

- Brush: the appropriate good type.
- Roller: Soft woolen roller.
- Any other tool that achieves the implementation of the desired decoration model.

#### THINNER:

"Time Thinner 504"

#### THINNING RATIO:

- (10-15)% by volume when using application tools.
- It depends on weather conditions and application conditions when used. It depends on the weather conditions when used

#### APPLICATION GUIDE:

- All new concrete surfaces need a period of time of no less than 28 days to dry completely before applying the primer.
- Old paint must be completely removed from previously painted surfaces
- It is free of holes, pits, burrs and any fragile areas.
- The surface must be solid
- You must ensure that the surface is clean, dry, and free of excesses, dirt, dust, grease, oils, salts, and mold.
- Treat small cracks and holes with a suitable filler such as "Time Ultimate," "Time Crack Filler," or "Time Epoxy Crack Filler" before starting to paint the base.
- (Consult technical support department)

#### Application instructions:

- The temperature during application must not be less than 5°C, the surface humidity must not exceed 8%, and the ambient relative humidity must not exceed 70%.
- The surface alkalinity must not exceed (pH=9).
- The paint must be stirred well before use.
- A sufficient amount of "Time Thinner 504" diluent can be added to obtain the appropriate viscosity for the application.
- Do not paint over wet surfaces until they are completely dry
- Taking into account the minimum time between coating the two layers.
- Do not paint the next layer unless the previous layer is completely dry
- Adequate ventilation should be provided during application.

#### PAINTING SYSTEM:

- Apply one coat of "Time Sealerin".
- Apply two coats of "Time Putty".
- Apply two coats of "Time Semi-Gloss Timeal", allow for full dry.
- Apply one coat of "Time Fantasy".
- Carry out the required design within 2 hours after application, depending on weather conditions.

#### SHELF LIFE:

1 liter bottle

In sealed container: 12 months in dry, cool and well ventilated place.

#### SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.

