

DESCRIPTION:

A high-quality final spray paint based on acrylic emulsions. It gives an attractive and strong appearance with elegant and consistent decorative lines in one layer.

CHARACTERISTICS:

- High resistance to moisture, heat and harsh weather conditions.
- High resistance to friction and scratching.
- Ease of application and formation.
- Excellent color stability.
- Excellent adhesion to surfaces.

RECOMMENDED USE:

It is used in exterior and interior applications on concrete, cement and clay brick surfaces of educational, residential, commercial and industrial buildings.

PHYSICAL CONSTANTS:

- The appearance is matte, sprayed in decorative grooves.
 - Color according to the colors of the "Al Jazeera Lintex" catalogue.
 - Specific gravity 1.9 2196D ASTM.
 - Viscosity: High viscosity.
 - Steel weight 80% ASTM 2697D.
- 2/kg at a thickness of (2300 - 2700 - 3000) microns
- Theoretical diffusion rate* (0.27 - 0.3 - 0.35) m
 - Volatile organic substances 15.3 g/l.

DRYING TIME:

- Surface drying: two hours
- Hard dry: 24 hours
- Complete dryness: 7 days
- Interval time: minimum 24 hours (if desired) maximum limit not specified

Previous results under ASTM 5895 at 25°C

APPLICATION TOOLS:

- Metal rulers
- Plastic barwa

THINNER:

Recommended Thinner is " Tap Water".

THINNING RATIO:

Ready to use.

A ratio of (1-2)% of fresh water can be used for dilution if necessary.

It depends on the nature of the weather and implementation conditions.

CLEANING TOOLS:

Tap Water.

APPLICATION GUIDE:

Surface preparation:

To dry completely before applying foundation.

- All new concrete surfaces require a period of no less than 28 days
- Old paint must be completely removed from previously painted surfaces
- The surface must be solid and free of holes, gouges, burrs and any fragile areas.
- You must ensure that the surface is clean, dry, and free of excesses, dirt, dust, grease, oils, salts, and mold.
- Treating cracks and small holes with a suitable filler such as "Time Ultimate," "Time Crack Filler," or "Time Epoxy Crack Filler 400" before starting to paint.

Basis "Consult the technical support department"

Application instructions:

- The temperature during application must not be less than 5°C, the surface humidity must not exceed 8%, and the ambient relative humidity must not exceed 70%.
- The surface alkalinity must not exceed (pH=9).
- The paint must be stirred well before use
- A sufficient amount of "fresh water" can be added to obtain the appropriate viscosity for the application.
- Do not paint over wet surfaces until they are completely dry

Taking into account the minimum time between coating the two layers.

- Do not paint the next layer unless the previous layer dries completely
- Avoid application in windy and rainy weather, at high temperatures, as well as under direct sunlight.
- Apply a layer of "Time Sealerx" according to the color of "Time Lintex" and leave it until dry.
- Apply one layer of "Time Lintex" using two metal trowels.
- Forming the desired appearance using the plastic brush, and cleaning the brush of stuck-on particles with a sponge saturated with water when necessary during shaping.

(as you like).

- The surface is smoothed and coordinated with a plastic brush to give a harmonious aesthetic shape and appearance

comments :

1 - To achieve the rate of spread and to obtain the desired shape, the "Time Lintex" painting process must be carried out by a professional painter.

2- Firm pressure must be applied with a ruler or trowel during application to obtain high adhesion.

3- Surfaces that take a circular shape must be given special attention when applying the coating.

PACKING:

25.88 KG DRUM

SHELF LIFE:

In sealed container: 12 months in dry, cool and well ventilated place

SPECIAL INSTRUCTIONS:

1. Paint should be stirred carefully before use.
2. A suitable quantity of Water can be added to get reasonable viscosity for application.
3. Do not apply on wet and moistened surfaces until get completely dry.
4. Do not apply the next coat unless the previous one is fully dry, minimum recoating interval time should be given between the two coats.
5. Should be used in well-ventilated place and far from children reach.
6. Surface temperature required during application must not be less than 10°C; the surface moisture should not exceed 8% and the relative humidity at work place not to exceed 70%.

SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.