

DESCRIPTION:

A high-quality final spray paint based on acrylic emulsions. It gives an attractive and strong appearance with elegant and consistent decorative lines in one layer.

CHARACTERISTICS:

- High resistance to moisture, heat and harsh weather conditions.
- High resistance to friction and scratching.
- Ease of application and formation.
- Excellent color stability.
- Excellent adhesion to surfaces.

RECOMMENDED USE:

It is used in exterior and interior applications on concrete, cement and clay brick surfaces of educational, residential, commercial and industrial buildings.

PHYSICAL CONSTANTS:

- The appearance is matte, sprayed in decorative grooves.
- Color according to the colors of the "Al Jazeera Lintex" catalogue.
- Specific gravity 1.9 2196D ASTM.
- Viscosity: High viscosity.
- Steel weight 80% ASTM 2697D.
- Theoretical diffusion rate* (0.27 - 0.3 - 0.35) m²/kg at a thickness of (2300 - 2700 - 3000) microns
- Volatile organic substances 15.3 g/l.

DRYING TIME:

- Surface drying: two hours
 - Hard dry: 24 hours
 - Complete dryness: 7 days
 - Interval time: minimum 24 hours (if desired) maximum limit not specified
- Previous results under ASTM 5895 at 25°C

APPLICATION TOOLS:

- Metal rulers
- Plastic barwa

THINNER:

Recommended Thinner is " Tap Water".

THINNING RATIO:

- Ready to use.
 - A ratio of (1-2)% of fresh water can be used for dilution if necessary.
- It depends on the nature of the weather and implementation conditions.

CLEANING TOOLS:

Tap Water.

APPLICATION GUIDE:

Surface preparation:

- To dry completely before applying foundation.
- All new concrete surfaces require a period of no less than 28 days
- Old paint must be completely removed from previously painted surfaces
- The surface must be solid and free of holes, gouges, burrs and any fragile areas.
- You must ensure that the surface is clean, dry, and free of excesses, dirt, dust, grease, oils, salts, and mold.
- Treating cracks and small holes with a suitable filler such as "Time Ultimate," "Time Crack Filler," or "Time Epoxy Crack Filler 400" before starting to paint.
- Basis "Consult the technical support department"

APPLICATION INSTRUCTIONS:

- The temperature during application must not be less than 5°C, the surface humidity must not exceed 8%, and the ambient relative humidity must not exceed 70%.
 - The surface alkalinity must not exceed (pH=9).
 - The paint must be stirred well before use
 - A sufficient amount of "fresh water" can be added to obtain the appropriate viscosity for the application.
 - Do not paint over wet surfaces until they are completely dry
 - Taking into account the minimum time between coating the two layers.
 - Do not paint the next layer unless the previous layer dries completely
 - Avoid application in windy and rainy weather, at high temperatures, as well as under direct sunlight.
 - Apply a layer of "Time Sealerx" according to the color of "Time Linetex" and leave it until dry.
 - Apply one layer of "Time Linetex" using two metal trowels.
 - Forming the desired appearance using the plastic brush, and cleaning the brush of stuck-on particles with a sponge saturated with water when necessary during shaping.
 - (as you like).
 - The surface is smoothed and coordinated with a plastic brush to give a harmonious aesthetic shape and appearance
 - comments :
1. To achieve the rate of spread and to obtain the desired shape, the "Time Linetex" painting process must be carried out by a professional painter.
 2. Firm pressure must be applied with a ruler or trowel during application to obtain high adhesion.
 3. Surfaces that take a circular shape must be given special attention when applying the coating

PACKING:

25.88 KG DRUM

SHELF LIFE:

In sealed container: 12 months in dry, cool and well ventilated place

SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.