

DESCRIPTION:

A high-quality decorative water-based paint based on a unique blend of special types of acrylic emulsions with special-effect colorants to give a beautiful appearance.

CHARACTERISTICS:

- Possibility of designing in multiple shapes
- The walls have a nice appearance
- Excellent metallic appearance
- Very good adhesion strength and high durability
- Good washability and color stability

RECOMMENDED USE:

It is used for interior applications on concrete and cement surfaces of palaces, offices, showrooms, hotels, restaurants, entrances to luxury homes, etc.

PHYSICAL CONSTANTS:

- Appearance has a slight shine
- Color according to the colors of the "Time Onyx" catalogue.
- Specific gravity 1.07, ASTM D1475
- Viscosity 30, ASTM D562
- Solid volume 27.20%, ASTM D2697
- The thickness of the dry layer is 90 microns per layer
- Theoretical diffusion rate* 3 m²/litre

the exams:

- Stability to freezing passing, ASTM D2243
- Stability to heat passing, ASTM D2243
- Chemical resistance (household detergents), ASTM D1308
- Water resistance passes ASTM D870
- (To avoid wastage, you must ensure, when purchasing, that the amount of paint is appropriate for the surfaces to be painted)

Application instructions:

The temperature during application must not be less than 5°C, the surface humidity must not exceed 8%, and the ambient relative humidity must not exceed 70%.

The surface alkalinity must not exceed (Ph=9).

The paint must be stirred well before use

Do not paint over wet surfaces until they are completely dry

Taking into account the minimum time between coating the two layers

Do not paint the next layer unless the previous layer is completely dry

Adequate ventilation should be provided during application

Surface preparation:

All new concrete surfaces need a period of time of no less than 28 days to dry completely before applying the primer

Old paint must be completely removed from previously painted surfaces

The surface must be solid and free of holes, gouges, burrs and any fragile areas

You must ensure that the surface is clean, dry and free of debris, dirt, dust, grease, oils, salts and mold. Treating small cracks and holes with a suitable diluent material such as "Time Ultimate" or "Time Crack Filler" before starting to paint the foundation.

APPLICATION TOOLS:

- Roller: Soft wool roller for lightly coating the first layer until it hides the surface it is applied to
- Putty knife: special type.
- Marine sponges & natural sponges

THINNER:

- Do not dilute
- Ready to use

THINNING RATIO:

- Do not dilute
- Ready to use

CLEANING TOOLS:

Tap Water.

APPLICATION GUIDE:

- Application guide: One coat of "Time Sealerin"
- Apply two layers of "Time Putty" and leave to dry completely
- Apply one or two layers of "Time D Silk Primer" according to the color specified in the product catalog and leave to dry completely.
- Apply one layer of "Time Onyx" with the roller and leave for 4-6 hours to dry.
- Apply a second layer of "Time Onyx" using a special putty knife or trowel to implement the desired design
- The required design must be implemented within a period of time not exceeding 10 minutes
- Another application method:
- One layer of "Time Sealerin" paint
- Apply two layers of "Time Putty" and leave to dry completely
- Apply one or two layers of "Time De Primer Silk" according to the color specified in the Time Chamois catalog and leave it to dry completely.
- "Time Onyx" applies
- The second color is marine sponge. The first color is marine sponge
- The third color is marine sponge
- All colors are touched gently with a regular surface sponge to give smoothness to the entire surface

PACKING:

- US Gallon 3.6 ltr

SHELF LIFE:

In sealed container: 12 months in dry, cool and well ventilated place

SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.