

DESCRIPTION:

A high-quality decorative water-based paint based on a unique blend of special types of acrylic emulsions with special-effect colorants to give a beautiful appearance.

CHARACTERISTICS:

- Possibility of designing in multiple shapes
- The walls have a nice appearance
- Excellent metallic appearance
- Very good adhesion strength and high durability
- Good washability and color stability

RECOMMENDED USE:

It is used for interior applications on concrete and cement surfaces of palaces, offices, showrooms, hotels, restaurants, entrances to luxury homes, etc.

PHYSICAL CONSTANTS:

- Appearance has a slight shine
- Color according to the colors of the "Time Onyx" catalogue.
- Specific gravity 1.07, ASTM D1475
- Viscosity 30, ASTM D562
- Solid volume 27.20%, ASTM D2697
- The thickness of the dry layer is 90 microns per layer
- Theoretical diffusion rate* 3 m²/litre
- the exams:
- Stability to freezing passing, ASTM D2243
- Stability to heat passing, ASTM D2243
- Chemical resistance (household detergents), ASTM D1308
- Water resistance passes ASTM D870
- (To avoid wastage, you must ensure, when purchasing, that the amount of paint is appropriate for the surfaces to be painted)

Application instructions:

- The temperature during application must not be less than 5°C, the surface humidity must not exceed 8%, and the ambient relative humidity must not exceed 70%.
- The surface alkalinity must not exceed (Ph=9).
- The paint must be stirred well before use
- Do not paint over wet surfaces until they are completely dry
- Taking into account the minimum time between coating the two layers
- Do not paint the next layer unless the previous layer is completely dry
- Adequate ventilation should be provided during application

SURFACE PREPARATION:

- All new concrete surfaces need a period of time of no less than 28 days to dry completely before applying the primer
- Old paint must be completely removed from previously painted surfaces
- The surface must be solid and free of holes, gouges, burrs and any fragile areas
- You must ensure that the surface is clean, dry and free of debris, dirt, dust, grease, oils, salts and mold.
- Treating small cracks and holes with a suitable diluent material such as "Time Ultimate" or "Time Crack Filler" before starting to paint the foundation.

APPLICATION TOOLS:

- Roller: Soft wool roller for lightly coating the first layer until it hides the surface it is applied to
- Putty knife: special type.
- Marine sponges & natural sponges

THINNER:

- Do not dilute
- Ready to use

CLEANING TOOLS:

Tap Water.

APPLICATION GUIDE:

- Application guide: One coat of "Time Sealerin"
- Apply two layers of "Time Putty" and leave to dry completely
- Apply one or two layers of "Time D Silk Primer" according to the color specified in the product catalog and leave to dry completely.
- Apply one layer of "Time Onyx" with the roller and leave for 4-6 hours to dry.
- Apply a second layer of "Time Onyx" using a special putty knife or trowel to implement the desired design
- The required design must be implemented within a period of time not exceeding 10 minutes

Another application method:

- One layer of "Time Sealerin" paint
- Apply two layers of "Time Putty" and leave to dry completely
- Apply one or two layers of "Time De Primer Silk" according to the color specified in the Time Chamois catalog and leave it to dry completely.
- "Time Onyx" applies
- The second color is marine sponge. The first color is marine sponge
- The third color is marine sponge
- All colors are touched gently with a regular surface sponge to give smoothness to the entire surface

PACKING:

US Gallon 3.6 ltr

SHELF LIFE:

In sealed container: 12 months in dry, cool and well ventilated place

SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.