

DESCRIPTION:

A high-end decorative water-based paint, based on an effective group of acrylic emulsions and a special type of fillers, which gives a beautiful and attractive marble appearance.

CHARACTERISTICS:

- Luxury spray appearance
- Excellent water resistance
- Excellent adhesion strength and high durability
- Easy to apply with beautiful shapes as desired
- Any decorative paint can be applied to it

RECOMMENDED USE:

It is used in internal applications on concrete, cement and gypsum surfaces of palaces, offices, halls, showrooms, hotels and restaurants. It can be used in bathrooms, kitchens and others after using "Time Regal Clear".

PHYSICAL CONSTANTS:

- Appearance has a slight shine
- Color according to the colors of the "Time Regal" catalogue.
- Specific gravity 1.60, ASTM D1475
- Viscosity: High viscosity, ASTM D562
- Solid volume 29%, ASTM D2697
- The thickness of the dry layer is 40 microns per layer
- Theoretical diffusion rate* 4.4 m²/litre
- Volatile organic matter value: 52.33 g/L,
the exams:
- Stability to freezing passing, ASTM D2243
- Stability to heat passing, ASTM D1849
- Water resistance: Pass, ASTM D870

APPLICATION TOOLS:

Brush: special type

THINNER:

- Do not dilute
- Ready to use

Application instructions:

- All new concrete surfaces need a period of time of no less than 28 days to dry completely before applying the primer
- Old paint must be completely removed from previously painted surfaces
- The surface must be solid and free of holes, gouges, burrs and any fragile areas
- You must ensure that the surface is clean, dry and free of debris, dirt, dust, grease, oils, salts and mold.
- Treating small cracks and holes with a suitable diluent material such as "Time Ultimate" or "Time Crack Filler" before starting to paint the foundation.

- The temperature during application must not be less than 5°C, the surface humidity must not exceed 8%, and the ambient relative humidity must not exceed 70%.
- The surface alkalinity must not exceed (Ph=9).
- The paint must be stirred well before use
- Do not paint over wet surfaces until they are completely dry
- Do not paint the next layer unless the previous layer dries completely, taking into account the minimum time interval between painting the two layers
- Adequate ventilation should be provided during application

CLEANING TOOLS:

Tap Water.

APPLICATION GUIDE:

- One layer of "Time Sealerin" paint
- Apply two layers of "Time Putty" and leave to dry completely
- Apply one or two coats of "Time D Primer Silk" in the same color as "Time Regal".
- Apply one coat of "Time Regal" using a metal trowel or putty knife according to the selected color.
- Apply a second layer of "Time Regal" according to the desired shape, and other layers can be applied if desired to give multiple shapes and designs.
- When the texture begins to dry, start polishing the surface using a trowel or a cloth.
- To obtain a high shine, it is recommended to use "Time Regal Clear".
- It is recommended to use "Time Regal Clear" in areas where the paint is exposed to water.

PACKING:

- Package: 1 litre
- Gallon: 3 litres
- Barrel: 9 litres

SHELF LIFE:

In sealed container: 24 months in dry, cool and well ventilated place

SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.