

#### DESCRIPTION:

Decorative, final water-based paint based on pure acrylic emulsion and special colorants designed to give the desert dimension.

#### CHARACTERISTICS:

- Luxury spray appearance
- Excellent water resistance
- Excellent adhesion strength and high durability
- Easy to apply with beautiful shapes as desired
- Any decorative paint can be applied to it

#### RECOMMENDED USE:

It is used for interior applications on concrete, cement and gypsum surfaces in palaces, offices, showrooms, hotels, restaurants....

#### PHYSICAL CONSTANTS:

- Metallic appearance
- Color according to the colors of the "Time Rawaq" catalogue.
- Specific transmission: 1.05, ASTM D1475
- Viscosity: 95, ASTM D562
- Theoretical diffusion rate: (4-5) m<sup>2</sup>/liter per layer
- Heat stability: Pass, ASTM D2243

#### APPLICATION TOOLS:

- Brush: special type

#### THINNER:

- Do not dilute
- Ready to use

#### Application instructions:

- The temperature during application must not be less than 5°C, the surface humidity must not exceed 8%, and the ambient relative humidity must not exceed 70%.
- The surface alkalinity must not exceed (Ph=9).
- The paint must be stirred well before use.
- Do not paint over wet surfaces until they are completely dry
- Do not paint the next layer unless the previous layer dries completely, taking into account the minimum time interval between painting the two layers.
- Adequate ventilation should be provided during application.
- All new concrete surfaces require a period of no less than 28 days
- Old paint must be completely removed from previously painted surfaces
- The surface must be solid and free of holes, gouges, burrs and any fragile areas.
- You must ensure that the surface is clean, dry, and free of excesses, dirt, dust, grease, oils, salts, and mold.

#### CLEANING TOOLS:

Tap Water.

#### APPLICATION GUIDE:

- Paint one layer of "Time Sealerin".
- Apply two coats of "Time Putty".
- Apply two layers of "Time D Silk Primer" according to the specific color of the "Time Rong" product (final layer) using a fine roller or spray, as you must ensure that the surface is smooth and that no traces of roller marks remain.
- The color of the product should be "Time De Primer Semi-Gloss" according to the color of "Time Rong" (final layer).
- Always must
- Apply a layer of (Time Lust) in a diagonal or horizontal direction and in a zigzag motion using the recommended special brush.

#### PACKING:

Package: 3 ltr

#### SHELF LIFE:

In sealed container: 24 months in dry, cool and well ventilated place

#### SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
  - Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
  - It is recommended to use the product in well-ventilated places or use artificial ventilation
  - The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.