

TIME ROSHAN

11002777

DESCRIPTION:

A high-quality decorative water-based paint, based on acrylic emulsion preparations, characterized by high durability and exceptional appearance.

CHARACTERISTICS:

- Luxury spray appearance
- Excellent water resistance
- · Excellent adhesion strength and high durability
- · Easy to apply with beautiful shapes as desired
- · Any decorative paint can be applied to it

RECOMMENDED USE:

It is used for interior applications on concrete, cement and gypsum surfaces in palaces, offices, showrooms, hotels, restaurants

PHYSICAL CONSTANTS:

- Appearance: homogeneous grooves
- The color is produced in ASTM D1475 white
- Specific gravity 1.54 ± 0.02 ASTM D562
- Viscosity 0.02±1.48 MPa ASTM D2697
- Solid volume 44.66%
- The thickness of the dry layer is 200 microns per layer
- Theoretical diffusion rate* (2.5-2) m2/liter the exams:
- Stability to freezing passes ASTM D2243
- Heat stability passing ASTM D2243
- Water resistance exceeds ASTM D870

APPLICATION TOOLS:

- Soft roller.
- · Hard plastic brush plastic knife. Brush: the good and appropriate type

THINNER:

- Do not dilute
- Ready to use

CLEANING TOOLS:

Tap Water.

APPLICATION GUIDE:

- Apply one layer of "Time Sealerin".
- Apply two coats of "Time Putty".
- Apply a layer of "Time Roshan" with a soft roller to the appropriate thickness.



TIME ROSHAN

11002777

- The required shape is designed within 5-10 minutes using the recommended tools in order to complete the required design, taking into account the surrounding conditions.
- Leave it for 24 hours to dry, then sand the surface slightly, and then apply a thin layer of the chosen decorative paint to obtain the final appearance.

PACKING:

- US gallon
- 18 liter dram

SHELF LIFE:

In sealed container: 12 months in dry, cool and well ventilated place

SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- · Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.