

# TIME TEXTURE

11004670

## DESCRIPTION:

A high-quality, final rough spray paint based on acrylic preparations. It is characterized by its resistance to weather conditions and the properties of heat insulation and sound absorption.

## CHARACTERISTICS:

- Superior resistance to harsh weather conditions
- High water resistance
- Heat insulation properties
- Good sound insulation properties
- Superior durability
- It can be formed into several rough designs using a roller or spray gun
- Excellent adhesion strength
- Ease of application

## RECOMMENDED USE:

It is used for external and internal applications, on concrete and cement surfaces, clay bricks, and iron and galvanized iron surfaces for buildings of educational, residential, commercial and industrial institutions. It can be used on air conditioning duct sheets.

## PHYSICAL CONSTANTS:

- The appearance is matte, with a rough touch.
- Color according to the colors of the Time Nature catalogue.
- Specific gravity 1.90 ASTM D1475
- Viscosity: High viscosity. ASTM D562
- Solid size 62% ASTM D2697
- Theoretical diffusion rate (0.12 – 0.33) m<sup>2</sup>/kg

The practical spread rate of the applied product depends on the nature of the surface, the surrounding conditions, the method of application, the thickness of the actual dry layer of the product, and the rate of wastage. To avoid wastage, you must ensure - when purchasing - the amount of paint appropriate for the surfaces to be painted.

## DRYING TIME:

- Surface drying: two hours (depends on thickness)
  - Complete dryness: 7 days
  - Interval time: minimum 24 hours (if desired) maximum limit not specified
- Previous results under ASTM 5895 at 25°C

## APPLICATION TOOLS:

- Air spray gun: Suggested nozzle size: medium 6 mm
- Air pressure: 80-100 psi
- Roller: the appropriate type

## THINNER:

Recommended Thinner is " Tap Water".

# TIME TEXTURE

11004670

## THINNING RATIO:

- (3-5)% by volume, when using the spray gun for pneumatic application
- (1-3)% by volume, when using a roller and brush
- It depends on the weather conditions when used

## CLEANING TOOLS:

Tap Water.

## APPLICATION GUIDE:

For new concrete, cement and clay brick surfaces:

- All new surfaces need a period of time of no less than 28 days to dry
- Excess sanding dust on the surface must be removed using a cloth or compressed air
- Apply one layer of "Time Sealerx" primer and leave it until it dries completely

For previously painted surfaces:

- Remove old paint if it is peeling or peeling
- Ensure that the surface is free of capers, oils, grease, dust and impurities
- Filling cracks and small holes with a suitable filler
- Apply one layer of "Time Sealerx" primer or a primer that matches it, according to the color of "Time Texture" and leave it to dry. Apply one layer of "Time Texture" using a spray gun or roller.

## PACKING:

25 KG. Drum.

## SHELF LIFE:

In sealed container: 12 months in dry, cool and well ventilated place

## SAFETY PRECAUTIONS:

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children

Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.