

#### DESCRIPTION:

A lightweight, easy-to-apply filler based on innovative emulsions. Specially designed to fill cracks and small holes up to 2 cm deep and 2 cm wide without any shrinkage or cracks and applied only once.

#### CHARACTERISTICS:

- Solvent-based and water-based paints can be applied to it.
- It is applied once and does not require more than one layer to fill.
- Does not require sanding.
- Gives a smooth surface
- High resistance to shrinkage.
- Resistant to cracking.
- It does not cause liquefaction, even if used on ceilings.

#### RECOMMENDED USE:

It is used to treat cracks and small holes up to 2 cm deep and 2 cm wide on concrete surfaces, plaster, gypsum surfaces, and clay bricks.

#### PHYSICAL CONSTANTS:

- Appearance: Light weight dough.
- Colour: white.
- Odor: very low
- Specific gravity: 0.38 ASTM 1475D.
- Volume of solids: 70%. ASTM 2697D.  
the exams:
- Heat and cold stability: Passing 3 ASTM 2243D courses.
- Shrinkage: Zero.
- Crack resistance: excellent.
- Filling range: for cracks up to 2 cm wide and 2 cm deep.

#### DRYING TIME:

- Surface drying (3-4 hours).
- Hard dehydration 48-72 hours
- The coating time is 48-72 hours
- Complete dryness for 24 hours

#### APPLICATION TOOLS:

- Putty knife

#### THINNER:

Ready to use

**APPLICATION GUIDE:**

- One layer of "Time Ultimate" is applied to fill cracks and small holes up to 2 cm deep and 2 cm wide.
- Most solvent and water based paints are applied to it

**PACKING:**

0.6 liter bottle.

**SHELF LIFE:**

In sealed container: 24 months in dry, cool and well ventilated place.

**SAFETY PRECAUTIONS:**

Please read and follow the health and safety instructions on the packaging as well as the warning instructions in the MSDS for this product

- The product must be handled with caution before and during application
- Contact of the paint with eyes and skin or inhalation of its spray and vapors must be avoided during application
- It is recommended to use the product in well-ventilated places or use artificial ventilation
- The product must be kept out of the reach of children
- Please hand over leftover paint and surplus containers to any approved local entity for the purpose of use or recycling for the sake of environmental safety.

Note: Waste and empty containers are disposed of in accordance with local regulations specified in the Pollution Control and Environmental Protection Laws.