

Time Regal

TA-16005

Description

A luxury-class water-borne decorative paint based on an efficient combination of a special kind of emulsion and filler to give an attractive and beautiful marble appearance.

Recommended Use

Recommended to use for interior applications on concrete, cement and gypsum surfaces of palaces, offices, showrooms, galleries, hotels, restaurants, it can be used in bathrooms and kitchens after applying "Time Regal Clear".

Characteristics

- Imparts great marble appearance.
- Excellent color stability.
- Multi uses after applying "Time Regal Clear".
- Easy to apply.

Physical Constants

Finish	Marble design.	-
Color	As per "Time Regal" catalog.	-
Specific Gravity	1.60± 0.02	ASTM D1475.
Viscosity	High viscous	ASTM D562.
Volume Solid	29 %.	ASTM D2697.
D.F.T.	40 μ.	-
Theoretical Spreading Rate*	65 μ for each coat. 4.4 m ² /Ltr	-
VOC	52.33 g/L.	-

(*) The practical spreading rate of the product depends on the surface, ambient temperature, application method, actual DFT and the wasted amount. (To avoid waste, be sure to buy the right amount of the paint for the required surface area)

Tests

Freeze-Thaw stability	Pass	ASTM D2243
Heater stability	Pass	ASTM D1849
Water Resistance	Pass	ASTM D870

Time Regal

TA-16005

Surface Preparation

- All new surfaces shall be cured at least 28 days prior to application of the primer.
- Remove old paints completely from previously painted surfaces.
- The substrate should have sufficient strength and free from unsounded areas, pug holes, protrusions and pops.
- Make sure that the surface is clean, dry, free from dust, oil, grease, salt and mold.
- Fill the holes and cracks with suitable fillers such as "Time Ultimate", "Time Crack Filler" or "Time Epoxy Crack Filler" prior to application of the primer (Refer to TSD).

Application Guide

- The required temperature during application, must not be less than 5°C; the surface moisture should not exceed 8% and the relative humidity at work place should not exceed 70%.
- pH of surface should not exceed 9.
- Paint should be stirred carefully before use.
- Do not apply on wet and moistened surfaces until completely dry.
- Do not apply the next coat unless the previous one is fully dry. Minimum recoating interval time should be followed.
- Adequate ventilation should be provided during application.

Application Tools

- Steel trowel: Special type.
- Putty knife.

Thinner

Not recommended.

Thinning Ratio

Ready to use

Painting System

- Apply one coat of "Time Sealerin"
- Apply two coats of "Time Putty".
- Apply one or two coats of "Time D Primer Silk" as the same color of "Time Regal".
- Apply one coat of "Time Regal" according to the required color, by using steel trowel or putty knife.
- Apply second coat of "Time Regal" according to the required design, other coats can be applied in case of giving forms and multiple designs.
- During the surface dry, start shining the surface by using a trowel or cotton cloth.
- For high gloss you can use "Time Regal Clear" .
- "Time Regal Clear" is recommended where the paint is exposed to water.

Time Regal

TA-16005

Drying Time

- Surface dry : (12 - 15) minutes.
- Hard dry : (2 - 3) hours.
- Full cure : 7 days.

All above test results according to ASTM D5895 @ 25°C.

Cleaning Tools

Tap Water.

Packing

- Can : 1 Ltr.
- Gallon : 3 Ltr.
- Drum : 9 Ltr.

Shelf Life & Storage

Shelf life: 12 months @ 25 °C.

Storage: The container should be kept in sealed, dry, cool, well-ventilated place and stored in accordance with national regulations.

Safety Precaution

- Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product.
- Handle with care before and during use.
- During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided.
- Recommended to use the product in well-ventilated area when applying the paint in insufficient ventilated areas, forced ventilation should be provided.
- Keep away from the reach of children.

For environmental safety : please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.

Time Regal

TA-16005

Disclaimer

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Al-Daman Building Materials Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Timepaints TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Timepaints quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.