

## Time Timestic

TA-18001

### Description

A water base gloss emulsion paint. Specially designed for exterior and interior applications in all weather conditions.

### Recommended Use

Recommended to use for exterior and interior applications where glossy and smooth touch is required on concrete, cement, gypsum and brick surfaces. Also can be applied over textures.

### Characteristics

- Very good gloss.
- High intensity and durability.
- Resists different weather conditions.
- High flexibility.
- Good water, alkali and salt resistance.
- Washable with water and soft detergents.
- Very good colour retention property.

## Time Timestic

TA-18001

### Physical Constants

Finish	Glossy.	-
Gloss	Above 60 at an angle of 60°	ASTM D-523.
Colour	Produced in white and other colours of "Time Paints" Colour card.	-
Specific Gravity	1.25 at temperature of 25°C	ASTM D-1475.
Viscosity	95 KU at temperature of 25°C	ASTM D-562.
Volume Solid	48.86 %	ASTM D-5201.
D.F.T.	Recommended D.F.T is 40 μ, each coat.	-
Spreading Rate	Theoretical spreading rate	12 m <sup>2</sup> /L at D.F.T. 40 μ.
Sagging	200 μ	ASTM D-4400.
Water Resistance	Pass, 7 days	ASTM D-870.
Alkali Resistance	Pass, 7 days (1 % solution)	ASTM D-1308.
Salt Resistance	Pass, 7 days (1.5 % solution)	ASTM D-1308.
Adhesion	Pass	ASTM D-3359.
Flexibility	Pass, 3 mm. Diameter	ASTM D-522.
Freeze-Thaw Stability Pass, 3 cycles	ASTM D-2243.	
Heater Stability	Pass, 49 days at 50°C.	-

### Surface Preparation

- Prepare the surface by cleaning it properly.
- For old surfaces. Remove all old paints and make sure that the surface is free from dust, oil, grease and other dirt.

### Application Tools

- **Spray Gun:** Recommended Nozzle size: (1.5 – 1.8) mm.
- **Roller:** Recommended Type: Soft and smooth woolen roller.
- **Brush:** General / Normal type.

## Time Timestic

TA-18001

### Thinner

Recommended Thinner is "Tap Water".

### Thinning Ratio

(25 - 35)% by volume for Spray Gun applications.

(15 - 25)% by volume for Roller & Brush applications.

Depends on the weather conditions at work place

### Painting System

For Exterior Surfaces:

- Apply one coat of "Time Sealerx" or "Time C Primer" or any other suitable type of Time primer and leave for full dry.
- Apply two coats of "Time Timestic".

For Interior Surfaces:

- Apply one coat of "Time Sealerin" or "Time C Primer" or any other suitable type of Time primer and leave for full dry.
- Apply two coats of "Time Crack Filler" or "Time Putty" or "Time Gypsonat" for gypsum surfaces, then sand the surface with sanding paper and clean the dust coming from the sanding by dry cloth or air blower.
- Apply two coats of "Time Timestic".

For texture finish (exterior & interior):

- Apply one coat of "Time Sealerin" (interior) or "Time Sealerx" (exterior)
- Apply one coat of texture paint and allow it for full dry.
- Apply two coats of "Time Timestic"

### Drying Time

- **Surface Dry** : 1 hour.
- **Full Dry** : 4 hours.
- **Recoat Interval** : 8 hours (minimum).

All above results according to ASTM D-5895.

### Cleaning Tools

Tap Water

### Packing

- US Gallon.
- 18 Ltr. Drum.

## Time Timestic

TA-18001

### Shelf Life & Storage

In sealed container: 12 months in dry, cool and well ventilated place.

### Safety Precaution

- Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product.
- Handle with care before and during use.
- During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided.
- Recommended to use the product in well-ventilated area when applying the paint in insufficient ventilated areas, forced ventilation should be provided.
- Keep away from the reach of children.

**For environmental safety :** please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.

### Disclaimer

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Al-Daman Building Materials Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Timepaints TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Timepaints quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.