

## Time Timetex

TA-25012

### Description

A soft finish texture based on acrylic emulsion provides different pressable granular designs, with a beautiful and attractive appearance.

### Recommended Use

Recommended to use for exterior and interior applications on concrete, cement and brick surfaces of educational institutions, residential, commercial and industrial buildings.

### Characteristics

- Can be formed in different designs with a beautiful appearance.
- High resistance to different weather conditions.
- Highly durable and excellent adhesion.
- Excellent resistance to water.
- High resistance to abrasion.

### Certificates

- In accordance with SASO standard No.: 2626/2017.

### Physical Constants

Finish	Flat, Soft Texture.	-
Color	White and other limited colors as per Timepaints color card.	-
Specific Gravity	1.85,	ASTM D1475
Viscosity	(6.5 – 7.5) x 1000 mPas.	ASTM D562
Volume solid	60%,	ASTM D2697.
Theoretical Spreading Rate*	(1-2-3) m <sup>2</sup> / Kg.	-
VOC	57.85 g/ltr.	-

### Tests

- MPI Meets standard # 42

(\*) The practical spreading rate of the product depends on the surface, ambient temperature, application method, actual DFT and the wasted amount.

(To avoid waste, be sure to buy the right amount of the paint for the required surface area).

## Time Timetex

TA-25012

### Surface Preparation

- All new surfaces shall be cured at least 28 days prior to application of the primer.
- Remove old paints completely from previously painted surfaces.
- The substrate should have sufficient strength and free from unsounded areas, pug holes, protrusions and pops.
- Make sure that the surface is clean, dry, free from dust, oil, grease, salt and mold.
- Fill the holes and cracks with suitable fillers such as "Time Ultimate", "Time Crack Filler" or "Time Epoxy Crack Filler" prior to application of the primer (Refer to TSD).

### Thinner

"Tap Water".

### Thinning Ratio

(5 – 7) % by volume for air spray application.

(3 - 5) % by volume for roller application.

All the above depending on the weather and application conditions

### Painting System

- Apply one coat of "Time Sealerx" according to "Time Timetex" color and leave for full dry.
- Apply one coat of "Time Timetex" using a spray gun or a roller.

### Drying Time

- **Surface dry** : 2 hrs. (Depending on the thickness).
- **Overcoating interval** : 24 hrs.(minimum) (if desired).
- **For pressing** : (20 – 30) minutes.
- **Full cure** : 7 days.

All above results according to ASTM D5895 @ 25°C.

### Cleaning Tools

Tap water.

### Packing

- 25 Kg. Drums.

### Shelf Life & Storage

**Shelf life** : 12 months @ 25 °C.

**Storage** : The container should be kept in sealed, dry, cool, well -ventilated place and stored in accordance with national regulations.

## Time Timetex

TA-25012

### Safety Precaution

- Please read and follow the precautionary notices displayed on the container, and all caution statements on the MSDS of this product.
- Handle with care before and during use.
- During application of paint, contact of liquid paint with eyes, skin, inhalation of paint mist and paint vapour, should be strongly avoided.
- Recommended to use the product in well-ventilated area when applying the paint in insufficient ventilated areas, forced ventilation should be provided.
- Keep away from the reach of children.

**For environmental safety :** please donate the leftover paint and packaging to your local authorized institution for usage or recycling purpose.

### Disclaimer

To the best of our knowledge the technical data listed herein is true and accurate up to publication date and is subject to change without prior notice. User must contact Al-Daman Building Materials Company to verify of any modifications before specifying or ordering the product. Thus, information given in this sheet is not intended to be exhaustive and any person using the product other than the recommendations in this sheet or without reverting to our Timepaints TSD, he should take his accountability in this connection.

As we are not capable to control the quality and the substrate's conditions as well as the factors that affect on using, or applying the product, so we never give any written or implied guarantee in these documents, but we guarantee our products to conform to Timepaints quality while we assume no responsibility for coverage, performance or injuries resulting from application. Liability "if any" is limited to replace the products mentioned above.